

# VOLTAS

A TATA Product

# VOLTAS

## Customized Branded Products



As a continuing policy of product innovation at VOLTAS, the above designs and specifications are subject to change without prior notice. The visuals of the product shown above are representative only. Actual product might differ from the one shown above.

Voltas 24x7 Customer Service - 1800 425 4555 (Toll Free) or SMS <AC> to 56677. [www.voltasac.com](http://www.voltasac.com)

**CORPORATE HEAD OFFICE:** Voltas Ltd, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044. Phone: 011 66505550. **BRANCHES:** **DELHI:** Voltas Ltd, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044. Phone: 011-66505550. **HARYANA:** Voltas Ltd, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi. Phone: 011-66505582. **GHAZIABAD:** Voltas Ltd, B-11/2, Site-3, Industrial Area, Meerut Road, Ghaziabad-201003, Phone: 0120-4155712. **CHANDIGARH:** Voltas Ltd, SCO NO. 201-203, 2<sup>nd</sup> Floor Sector 34 A, Chandigarh, Phone: 0172 6610116/17/20. **LUCKNOW:** Voltas Limited, Shalimar Titanium, Block - C, 4th floor, Office Nos. 410 - 412, Plot No. TCG -1/1, Opp. Indira Gandhi Pratishthan, Vibhuti Khand, Gomti Nagar, Lucknow - 226 010, Phone: 0522-6566961. **JAIPUR:** Voltas Ltd, Diamond Tower, 201-203, Purani Chungi, Ajmer Road, Jaipur-302017, Phone: 0141-6451747/48. **HYDERABAD:** Voltas Ltd, 7-2-1735, Saathinagar, Hyderabad-500018. Phone: 040-66743001. **BANGALORE:** Voltas Ltd, 7th Floor, 701- Pride Hulkul 116, Lalbagh Road, Bangalore- 560027, Phone: 08022535600. **CHENNAI:** Voltas Ltd, No. 264, Anna Salai, Chennai - 600018, Phone: 66760333/11. **KOCHI:** Voltas Ltd, Ambanat building, 39/3522, M.G. Road, Ravipuram, Kochi-682016, Phone: 0484-6605555. **COIMBATORE:** Voltas Ltd, 24-2, Pykara Office Road, Tatabad, Coimbatore-6410102, Phone: 0422-6502419/6530080. **MUMBAI:** Voltas Ltd, Voltas House B, 2nd Floor, T.B. Kadam Marg, Chinchpokli, Mumbai - 400033, Phone: 022-66656333. **PUNE:** Voltas Ltd, Equitorial Forum, 2<sup>nd</sup> & 3<sup>rd</sup> Floor, Mumbai-Pune Road, Wakadewadi, Pune-411003, Phone: 020-66011776. **THANE:** Voltas Ltd, Unit II, 1<sup>st</sup> Floor, 2<sup>nd</sup> Pokhran Road, Thane-400601, Phone: 022-67920106/07. **AHMEDABAD:** Voltas Ltd, A-301, Shivalik Corporate Park, Shivranjini Crossroad Satellite, Ahmedabad- 380015, Phone: 0790-66301190/91. **INDORE:** Voltas Ltd, The View, 305, Y.N. Road, 3<sup>rd</sup> Floor, South Tukoganj Thana, Indore-452001, Phone: 0731-4046393/4043512. **KOLKATA:** Voltas Ltd, Gilanders House, A Block, 2<sup>nd</sup> Floor, 8 N.S. Road, Kolkata-700001, Phone: 033-66266207. For Institutional Inquiry - 09163362409. **PATNA:** Voltas Ltd, Maharaja Complex, 306-A, 3<sup>rd</sup> Floor, Frazer Road, Patna-800001, Phone: 0612-3222555/6455192. For Institutional Inquiry - 09431104056. **JAMSHEDPUR:** Voltas House, 3<sup>rd</sup> Floor, Main Road, Bistupur, Jamshedpur - 831001, Phone: 0657-6455921. For Institutional Inquiry - 09771491152. **BHUBANESWAR:** Voltas Ltd, B-15, 2<sup>nd</sup> Floor, Arihant Plaza, Shaheed Nagar, Bhubaneswar-751007, Phone: 0674-2544919/18. For Institutional Inquiry - 09937140010.

Voltas adheres to the E-Waste (Management and Handling) Rules 2011, notified by the Ministry of Environment and Forests, Government of India. For more information on Voltas E-Waste and exchange policy please contact our E-Waste partner at 1800-419-3283.



## The most trusted way to profit from cooling.





### Horizontal Chest Freezers (Metal Top)

- Soft look designs for better appearance
- Stucco Aluminium inner liner for improved hygiene
- Castor wheels for easy transportation
- UV Grade plastic materials for long-lasting appearance
- CFC-free insulation for environment protection
- Pre-coated body for glossy finish
- Spring loaded hinges for effortless usage
- Signal indicator for storage protection in case of power failure
- Door lock for restricted accessibility
- Sunken handle for safer operation
- PUF insulation

### Horizontal Chest Cooler (Metal Top)

- Contemporary and sturdy design
- High density, high pressure 60mm insulation ensuring minimum heat ingress and low power consumption
- Corrosion resistant with outer body in pre-coated steel sheet
- Tropicalised and energy-efficient R 134a compressor
- Multiple door with sunken handles
- Spring-loaded hinges in doors
- Castor wheels for free and easy movement
- Elegant door trims
- Optional accessory
- Customised branding of machines



#### Technical Specifications for Metal Top Horizontal Chest Freezers (CFH)

S.NO.	Product description	90 L SD	120 L SD	205 L SD	320 L SD	320 L DD	405 L DD	500 L DD	600 L TD	EF-320 L-SD
1.	Insulating material	60 mm Thick Polyurethane Foam								
2.	Overall product dimensions (WxDxH) mm	550 x 565 x 830	670 x 565 x 830	835 x 665 x 830	1180 x 665 x 830	1180 x 665 x 830	1450 x 665 x 830	1680 x 665 x 830	1915 x 665 x 860	1180 x 665 x 830
3.	Packed dimensions (WxDxH) mm	610 x 620 x 880	725 x 620 x 880	895 x 720 x 880	1240x720 x 880	1240x720 x 880	1510 x 720 x 880	1740 x 720 x 880	2000 x 740 x 910	1240 x 740 x 880
4.	No. of baskets	NA	NA	1	1	1	2	2	2	-
5.	No. of doors	1	1	1	1	2	2	2	3	1

#### Technical Specifications for Metal Top Horizontal Coolers (CC)

S.NO.	Product description	90 L SD	120 L SD	205 L SD	320 L SD	320 L DD	405 L DD	500 L DD
1.	Rated power supply	230 Volts; 50 Hz ; 1 Ph						
2.	Overall product dimensions (WxDxH) mm	550 x 565 x 830	670 x 565 x 830	835 x 665 x 830	1180 x 665 x 830	1180 x 665 x 830	1450 x 665 x 830	1680 x 665 x 830
3.	Packed dimensions (WxDxH) mm	610 x 620 x 880	725 x 620 x 880	895 x 720 x 880	1240x720 x 880	1240x720 x 880	1510 x 720 x 880	1740 x 720 x 880
4.	Gross weight (Kg)	36.5	52.5	72	81	81	88.5	106
5.	Net weight (Kg)	30	43	56	68	68	74	90



### Horizontal Chest Freezers (Glass Top)

- Soft look designs for better appearance
- Stucco Aluminium inner liner for improved hygiene
- Castor wheels for easy transportation
- UV Grade plastic materials for long-lasting appearance
- CFC-free insulation for environment protection
- Pre-coated body for glossy finish
- Low emissivity glass for optimum cooling loss
- Signal indicator for storage protection in case of power failure
- Door lock for restricted accessibility
- PUF insulation

#### Technical Specifications for Glass Top Horizontal Freezers

S.NO.	Product description	205 GSL	320 GSL	405 GSL
1.	Insulating material	60 mm Thick Polyurethane Foam		
2.	Overall product dimensions (WxDxH) mm	848 x 635 x 815	1195 x 635 x 815	1465 x 635 x 815
3.	Packed dimensions (WxDxH) mm	895 x 720 x 880	1240 x 720 x 880	1510 x 720 x 880
4.	No. of sliding doors	2	2	2
5.	Storage baskets	Fabricated with wire construction painted epoxy liquid in white		

### Visi Cooler

- Sleek designs for better appearance
- Castor wheels for easy transportation
- UV Grade plastic materials for long-lasting appearance
- CFC-free insulation for environment protection
- Powder painted body for glossy finish
- Door lock for restricted accessibility
- Certified performance by international laboratories
- Two pane glass for optimum cooling loss
- Tropicalised compressors
- PUF insulation

#### Technical Specifications: Visi Cooler

S.NO.	Product specification	70 L SD	120 L SD	220 L SD	320 L SD	425 L SD
1.	No. of doors	1	1	1	1	1
2.	No. of 300 ml bottles	38	60+5 No. of 330 ML Cans	126	216	316
3.	No. of 650 ml bottles	10	16	30	90	150
4.	Overall package dimensions (WxDxH) mm	515x645x765	535x635x1100	595x720x1455	630x755x1745	735x710x2215
5.	Overall cabinet dimensions (WxDxH) mm	455x585x720	475x585x1060	535x670x1405	560x705x1700	650x635x2170

Insulation system 40 mm thick polyurethane foam made up with cfc-free blowing agent.

